

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-102699

(43)Date of publication of application : 13.04.1999

(51)Int.Cl.

H01M 4/38

H01M 4/02

H01M 10/40

(21)Application number : 09-261710 (71)Applicant : ASAHI CHEM IND CO LTD

(22)Date of filing : 26.09.1997 (72)Inventor : MIYAKE NAOTO
HASHIMOTO TOMOTAKA

(54) LITHIUM SECONDARY BATTERY AND NEGATIVE ELECTRODE USED THEREFOR

(57)Abstract:

PROBLEM TO BE SOLVED: To provide capacity higher than one using a carbon negative electrode by mainly using an intermetallic compound containing metal or semimetal of a 4B group as a negative electrode active material, and using an alloy containing at least one or more kinds of metals or semimetals except for an element to form the intermetallic compound.

SOLUTION: Sn and Pb are cited as metal of a 4B group, and Si and Ge are cited as semimetal of the 4B group. AsSn and AuSn exist as a material containing Sn. AuPb₂ and CaPb₃ exist as a material containing Pb. As₃GeLi₃ and CoFeGe exist as a material containing Ge. MgSnB_x and Mg₂SnF_e_x are cited as the composition of an alloy. In these, the other metallic element or a semimetallic element existing on a periphery of an intermetallic compound operates as a reinforcing material, and since a structure is maintained, the degradation such as pulverization of an active material caused by repetitive charge./discharge is hardly caused.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's
decision of rejection]

[Date of requesting appeal against
examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office